

NEW MODEL

INSERO HEATER



THE INSERO HEATER HT1010D PROVIDES HIGH PERFORMANCE, SELF-CONTAINED HEAT WITH FEATURES THAT IMPROVE EFFICIENCY.

- The new model incorporates a modified storage area with larger doors, making it more streamlined.
- Increased fuel capacity allows you to heat your jobsite longer.
- Options such as the light tower and gas detection, provide added jobsite productivity and safety.



INSERO
EQUIPMENT™

HEATER

HEAT FOR ANY APPLICATION

CONSTRUCTION

INDUSTRIAL

MINING

AGRICULTURE

AVIATION

MILITARY

SPECIAL EVENTS

RAILROAD

ENGINEERED INNOVATION

TECHNICAL SPECIFICATIONS

Height w. Exhaust Stacks	7.0 ft (2.1 m)
Width	7.3 ft (2.2 m)
Length	13.4 ft (4.1 m)
Weight Wet	6,100 lb (2,767 kg)
Weight Dry	4,500 lb (2,041 kg)
Fuel Capacity	220 gal (832 L)

ENGINE SPECIFICATIONS

Engine	Cat C1.5
Type	Diesel
Displacement	1.5 L
Aspiration	Naturally aspirated
HP	18.7 HP (14 KW) @ 1800 RPM
Emissions Compliance	Tier 4 Final

HEATER SPECIFICATIONS

Model	HT1010D
Heat Output (each)	500,000 BTU/HR
Max Air Flow (each)	3,250 CFM (1.5 m ³ /sec)
Discharge Air Temp.	185° F (85° C)
Max Duct Length	110 ft (33.4 m)
Total Heat Output	1,000,000 BTU/HR
Duct Diameter (each)	16 in (40.6 cm)

SERVICEABILITY & EFFICIENCY

- 220 gal (832 L) fuel tank capacity provides up to 24 hours of continuous run time
- Up to 115% containment
- Skid mounted burners slide out for easy access
- Hour meter and start/stop switch with automatic shutdown protection for low oil pressure and high coolant pressure
- Shore power connection capability improves fuel economy when electric power is available
- Return air capability to increase heating efficiency
- Equipped with large storage compartment
- Reliable starting power from a maintenance free 4D 12V battery with 1125 cold cranking amps
- Auxiliary 120 VAC (240V/ 50Hz) power outlet with GFCI and 20A service provides a powerful convenient power source
- Gas struts enable easy opening of heater doors for added safety and quick service access
- Trailer has adjustable height 3 in (7.6 cm) pintle hitch

OPTIONS

- Overspeed protection and combustible gas detection system for added safety in oil & gas operations
- Low fuel and engine power indicating strobe lights
- Roof mounted light tower with LED lights and 11.5 ft (3.5 m) telescoping tower. Remote control to raise/lower the tower and to rotate/tilt the lights
- Kubota diesel engine
- Cold weather package
- GPS option for equipment tracking
- Ducting and duct connectors available



*Optional light tower.



CONTACT AN INVERO SALES REPRESENTATIVE

+1 402.861.2970 | sales@inveroequipment.com

11002 SAPP BROTHERS DRIVE
OMAHA, NEBRASKA 68138